



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar
Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2
Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	38,2	
3,00 mm	h 7	32,9	(50,0)
4,00 mm	h 7	137,0	
5,00 mm	h 7	47,1	(200,0)
6,00 mm	h 8	353,3	(200,0)
8,00 mm	h 8	187,7	(200,0)
10,00 mm	h 8	800,4	
12,00 mm	h 8	626,8	
14,00 mm	h 8	309,8	
15,00 mm	h 8	391,9	(200,0)
16,00 mm	h 9	934,9	
18,00 mm	h 9	369,9	(200,0)
20,00 mm	h 9	1006,3	
22,00 mm	h 9	713,6	
25,00 mm	h 9	3074,9	
30,00 mm	h 9	227,5	(1100,0)
35,00 mm	h 9	980,0	
40,00 mm	-0/+0.100	667,3	(2000,0)
45,00 mm	-0/+0.100	857,6	(600,0)
50,00mm	-0/+0.100	1564,1	(600,0)
55,00 mm	-0/+0.100	4000,5	(200,0)
60,00 mm	-0/+0.120	4487,5	(200,0)
65,00 mm	-0/+0.120	369,5	
70,00 mm	-0/+0.140	557,4	(400,0)
		241,6	
80,00 mm	-0/+0.140	524,8	(400,0)
		237,0	
90,00 mm	-0/+0.200	742,7	(400,0)
100,00 mm	-0/+0.500	39,4	(735,0)
		120,6	(120,0)
110,00 mm	-0/+0.500	458,9	(400,0)
		290,1	
120,00 mm	-0/+0.500	578,0	(300,0)
130,00 mm	-0/+0.500	1393,5	(540,0)
140,00 mm	-0/+0.500	447,9	(1050,0)
150,00 mm	-0/+0.500	665,4	(480,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
160,00 mm	-0/+0.500	553,2	
170,00 mm	-0/+0.500	442,7	
180,00 mm	-0/+0.500	692,4	
190,00 mm	-0/+0.500	347,9	
200,00 mm	-0/+0.500	633,3	
225,00 mm	-0/+0.500	759,4	
250,00 mm	-0/+0.500	42,6	
280,00 mm	-0/+0.500	478,8	
305,00 mm	-0/+0.500	213,4	
305,00 mm	-0/+0.500	64,0	(390,0)
350,00 mm	-0/+0.500	527,6	

Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	306,8	
130,00 mm	-0/+0.500	236,8	

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	24,8	(20,0)
3,00 mm	h 7	98,9	(50,0)
4,00 mm	h 7	204,4	
5,00 mm	h 7	466,2	(1472,0)
6,00 mm	h 8	786,2	(1120,0)
8,00 mm	h 8	64,7	(1227,0)
10,00 mm	h 8	135,1	(1000,0)
12,00 mm	h 8	251,7	(1310,0)
14,00 mm	h 8	150,5	(200,0)
15,00 mm	h 8	323,9	
16,00 mm	h 9	506,8	(300,0)
18,00 mm	h 9	634,3	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
20,00 mm	h 9	1074,5	(1400,0)
22,00 mm	h 9	222,6	(400,0)
25,00 mm	h 9	1299,1	(2500,0)
		0,0	(203,0)
25,00 mm	h 9	394,0	(600,0)
30,00 mm	h 9	38,4	(1300,0)
		0,0	(925,1)
35,00 mm	h 9	654,1	(1300,0)
36,00 mm	h 9	938,4	
40,00 mm	-0/+0.100	252,0	(2800,0)
40,00 mm	-0/+0.100	144,1	(2000,0)
45,00 mm	-0/+0.100	489,8	(1300,0)
50,00 mm	-0/+0.100	1407,8	(500,0)
55,00 mm	-0/+0.100	628,6	(600,0)
60,00 mm	-0/+0.120	472,0	(1800,0)
65,00 mm	-0/+0.120	34,2	(1000,0)
70,00 mm	-0/+0.140	279,0	(1300,0)
75,00 mm	-0/+0.140	1056,9	
80,00 mm	-0/+0.140	762,3	(300,0)
		224,0	
90,00 mm	-0/+0.200	85,4	(600,0)
100,00 mm	-0/+0.500	1077,0	(915,0)
110,00 mm	-0/+0.500	452,3	(300,0)
120,00 mm	-0/+0.500	509,8	(300,0)
130,00 mm	-0/+0.500	1205,4	(500,0)
140,00 mm	-0/+0.500	1175,3	
150,00 mm	-0/+0.500	798,4	
160,00 mm	-0/+0.500	773,3	
170,00 mm	-0/+0.500	700,0	(600,0)
180,00 mm	-0/+0.500	329,9	(330,0)
200,00 mm	-0/+0.500	527,0	
225,00 mm	-0/+0.500	127,0	(360,0)
230,00 mm	-0/+0.500	436,2	
250,00 mm	-0/+0.500	34,1	(400,0)
		0,0	(461,0)
280,00 mm	-0/+0.500	792,0	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
305,00 mm	-0/+0.500	396,4	
330,00 mm		360,4	
350,00 mm	-0/+0.500	731,6	

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE

MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Contidition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
	0,0	(200,0)
	221,0	
0,6 x 1000 x 2500	6,8	(1320,0)
	0,0	(300,0)
0,8x 1000 x 2500	1341,5	
1,0 x 1250 x 3000	1203,3	(2000,0)
1,5 x 1250 x 3000	783,8	
2,0 x 1250 x 3000	178,4	
2,0 x 1250 x 3000	2488,0	
2,5 x 1250 x 3000	212,6	
3,0 x 1250 x 3000	497,6	
4,0 x 1000 x 2000	451,5	(200,0)
	252,6	
5,0 x 1000 x 2000	372,1	(200,0)
6,0 x 1000 x 2000	217,4	(200,0)

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017

PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
1,0x1000x2000	269,6	
	54,4	(200,0)
1,0x1000x2000	8,2	
1,5x1000x2000	80,9	(297,0)
	17,6	(169,0)
	167,7	(105,8)
2,0x1000x2000	292,2	(800,0)
3,0x1000x2000	344,1	(800,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017

PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
4,0x1000x2000	570,0	(400,0)
5,0x1000x2000	269,1	(200,0)
6,0x1000x2000	218,5	(259,0)
	205,0	(200,0)
8,0x1500x2500	0,0	(450,0)

Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1 x 1000 x 2000	143,4	(100,0)
1 x 1000 x 2000	148,5	
1 x 1000 x 2000	13,5	
	262,1	
	427,0	
	339,2	
2 x 1000 x 2000	63,1	(400,0)
	337,1	
	401,7	
3 x 1000 x 2000	231,1	
3 x 1000 x 2400	302,1	
3 x 1250 x 2500	43,2	
	492,0	
4 x 1000 x 2000	232,0	(300,0)
	311,0	(731,4)
5 x 1000 x 2000	355,5	(200,0)
	461,5	
	116,3	(200,0)
	0,0	(541,6)
	0,0	(632,0)
	150,5	(150,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	92,9	
12,7 x 12,7	197,2	
19,05 x 19,05	87,8	(300,0)
25,4 x 6,35	141,0	
25,4 x 12,7	39,8	
25,4 x 25,4	154,4	(300,0)

Titanium Grade 2 Welding wire

AWS A5.16 ERTi-2

Dimension	QTY (kg)	Incoming
1,2 mm	40,0	
1,2 mm	20,0	
2,0 mm	35,0	
2,4 mm	50,0	
3,2 mm	50,0	

Titanium Grade 5 Welding wire

AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
1,6 mm	9,8	
2,4 mm	10,0	