



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	48,5	
3,00 mm	h 7	44,8	
4,00 mm	h 7	27,5	
5,00 mm	h 7	150,2	
6,00 mm	h 8	475,7	(300,0)
8,00 mm	h 8	0,0	(300,0)
10,00 mm	h 8	518,9	(400,0)
12,00 mm	h 8	489,1	
14,00 mm	h 8	311,4	
15,00 mm	h 8	54,8	(300,0)
16,00 mm	h 9	456,5	(500,0)
18,00 mm	h 9	662,4	
20,00 mm	h 9	660,9	
22,00 mm	h 9	189,1	(400,0)
25,00 mm	h 9	2759,0	(1000,0)
30,00 mm	h 9	655,6	(1700,0)
35,00 mm	h 9	370,0	(700,0)
40,00 mm	-0/+0.100	1069,1	(600,0)
45,00 mm	-0/+0.100	322,1	(200,0)
50,00mm	-0/+0.100	853,9	(200,0)
55,00 mm	-0/+0.100	806,4	
60,00 mm	-0/+0.120	532,9	
65,00 mm	-0/+0.120	530,0	
70,00 mm	-0/+0.140	190,5	(400,0)
80,00 mm	-0/+0.140	609,5	
90,00 mm	-0/+0.200	38,3	(360,0)
100,00 mm	-0/+0.500	387,8	
110,00 mm	-0/+0.500	265,2	
120,00 mm	-0/+0.500	75,7	(200,0)
130,00 mm	-0/+0.500	6,5	(720,0)
140,00 mm	-0/+0.500	48,0	(1040,0)
150,00 mm	-0/+0.500	38,1	(240,0)
160,00 mm	-0/+0.500	206,2	
170,00 mm	-0/+0.500	430,4	
180,00 mm	-0/+0.500	231,3	



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
190,00 mm	-0/+0.500	128,5	
200,00 mm	-0/+0.500	324,8	
225,00 mm	-0/+0.500	327,7	
250,00 mm	-0/+0.500	265,8	
280,00 mm	-0/+0.500	193,0	(278,0)
305,00 mm	-0/+0.500	339,6	
305,00 mm	-0/+0.500	0,0	(310,0)
350,00 mm	-0/+0.500	56,2	(350,0)

## Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	328,0	
130,00 mm	-0/+0.500	236,8	

## Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	42,4	
3,00 mm	h 7	127,8	
4,00 mm	h 7	119,9	(300,0)
5,00 mm	h 7	276,0	(400,0)
6,00 mm	h 8	500,9	(600,0)
8,00 mm	h 8	372,2	(400,0)
10,00 mm	h 8	374,1	(600,0)
12,00 mm	h 8	445,8	(500,0)
14,00 mm	h 8	30,0	(300,0)
15,00 mm	h 8	95,4	(300,0)
16,00 mm	h 9	654,3	(300,0)
18,00 mm	h 9	411,8	(200,0)
20,00 mm	h 9	987,4	(800,0)
22,00 mm	h 9	339,4	
25,00 mm	h 9	1524,7	(300,0)
25,00 mm	h 9	165,9	(300,0)
30,00 mm	h 9	277,0	



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
35,00 mm	h 9	365,0	(800,0)
36,00 mm	h 9	81,4	(400,0)
40,00 mm	-0/+0.100	1202,6	(2500,0)
40,00 mm	-0/+0.100	1202,3	(2500,0)
45,00 mm	-0/+0.100	543,3	(200,0)
50,00 mm	-0/+0.100	1420,2	(150,0)
55,00 mm	-0/+0.100	290,1	
60,00 mm	-0/+0.120	361,4	(600,0)
65,00 mm	-0/+0.120	312,7	(300,0)
70,00 mm	-0/+0.140	480,0	
75,00 mm	-0/+0.140	552,6	
80,00 mm	-0/+0.140	540,9	
90,00 mm	-0/+0.200	540,3	
100,00 mm	-0/+0.500	1199,7	
110,00 mm	-0/+0.500	76,1	(400,0)
120,00 mm	-0/+0.500	496,8	
130,00 mm	-0/+0.500	757,8	(500,0)
140,00 mm	-0/+0.500	301,0	(420,0)
150,00 mm	-0/+0.500	292,0	
160,00 mm	-0/+0.500	146,6	(270,0)
170,00 mm	-0/+0.500	502,0	
180,00 mm	-0/+0.500	410,3	
190,00 mm	-0/+0.500	197,0	
200,00 mm	-0/+0.500	231,8	
225,00 mm	-0/+0.500	11,1	
230,00 mm	-0/+0.500	346,5	
250,00 mm	-0/+0.500	272,6	
280,00 mm	-0/+0.500	66,8	(140,0)
305,00 mm	-0/+0.500	209,0	
350,00 mm	-0/+0.500	259,0	

## Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Contidition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
-----------	----------	----------



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Condition: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
0,6 x 1000 x 2500	427,5	(442,0)
0,8x 1000 x 2500	136,7	(1488,0)
1,0 x 1250 x 3000	1358,2	(1503,0)
1,5 x 1250 x 3000	1002,9	
2,0 x 1250 x 3000	198,6	
2,0 x 1250 x 3000	1299,2	(668,0)
2,5 x 1250 x 3000	212,6	
3,0 x 1250 x 3000	918,2	
4,0 x 1000 x 2000	217,3	
5,0 x 1000 x 2000	282,2	
6,0 x 1000 x 2000	214,5	

## Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017  
PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
1,0x1000x2000	245,6	
1,0x1000x2000	8,2	
1,5x1000x2000	654,0	
2,0x1000x2000	948,7	
3,0x1000x2000	746,2	
4,0x1000x2000	287,2	
5,0x1000x2000	378,1	

## Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1 x 1000 x 2000	141,1	
1 x 1000 x 2000	92,4	
1 x 1000 x 2000	13,5	
2 x 1000 x 2000	213,7	
3 x 1000 x 2000	133,2	
3 x 1250 x 2500	41,4	
4 x 1000 x 2000	70,8	



# TITANIUM GATEWAY

STOCK AND SALES COMPANY FOR TITANIUM AND SPECIAL ALLOYS

## Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
5 x 1000 x 2000	91,6	

## Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	105,8	
12,7 x 12,7	161,9	
19,05 x 19,05	135,8	
25,4 x 6,35	151,4	
25,4 x 12,7	313,0	
25,4 x 25,4	224,4	

## Titanium Grade 2 Welding wire

AWS A5.16 ERTi-2

Dimension	QTY (kg)	Incoming
1,2 mm	15,0	
1,2 mm	15,0	
2,0 mm	10,0	(30,0)
2,4 mm	5,0	(30,0)
3,2 mm	15,0	(20,0)

## Titanium Grade 5 Welding wire

AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
1,6 mm	10,0	
2,4 mm	10,0	